

5" DRY MASONRY SAW, WITH DUST EXTRACTION



NEW TOOL OVERVIEW 4100KB



1
YEAR
WARRANTY
30
DAY SATISFACTION
GUARANTEE

FEATURES

- Saw attaches to optional guide rail with guide rail adapter (#198673-2) to provide straight and accurate cutting
- 1-3/8" (38mm) dust extraction port swivels 360° for convenient operation
- Lock-off button for user convenience
- Large rubberized depth gauge lever for easy adjustment
- Large top handle design for increased comfort
- Dust protected trigger switch helps prevent dust contamination for longer tool life

SPECIFICATIONS

AMPS	13
Watts Out	1,800
No Load Speed	12,200 RPM
Blade Diameter	5"
Max. Cutting Depth	1-9/16"
Arbor	13/16"
Overall Length	9-1/8"
Net Weight	6.6 lbs.
Shipping Weight	10.6 lbs.
UPC Code	088381-851428

PRODUCT HIGHLIGHTS



POWER

13 AMP motor delivers 12,200 RPM for the most demanding applications



CAPACITY

High depth of cut capacity up to 1-9/16" at 90°



VISIBILITY

Transparent upper guard dust cover for increased visibility



ACCURACY

Optional guide rail attaches to saw with guide rail adapter to provide accurate and straight cutting

STANDARD EQUIPMENT

- Hex Wrench (783203-8)
- Spanner Wrench (781041-2)
- Dust Bag (126738-0)

RELATED PRODUCTS

1. 5" Diamond Blade, Turbo, Hard Material (A-94605)
2. 5" Diamond Blade, Turbo, General Purpose (A-94568)
3. 55" Guide Rail (194368-5)
4. Guide Rail Adapter (198673-2)
5. Rail Clamp Set, 2-Pc. (194385-5)

