21° FULL ROUND HEAD 3-1/2" FRAMING NAILER



PRODUCT HIGHLIGHTS



CONTROL

2-mode selector switch allows operator to select contact or sequential nailing options



PRECISION

"Tool-less" depth adjustment engineered for more precise flush and countersink nailing



DURABILITY

Solid top-loading aluminum magazine for longer life



CONVENIENCE

Reversible hook allows tool to remain close by

777.akita NEW TOOL OVERVIEW AN924

FEATURES

- Faster nail driving speed for maximum performance
- Drives 21° plastic collated framing nails from 2" to 3 1/2" in length and .113 to .148 in diameter
- · Lightweight design at only 8.3 lbs.
- Front magazine cover for additional nail support
- Heat treated S7 steel driver blade for durability
- "Tool-less" depth adjustment engineered for more precise flush and countersink nailing
- Ergonomic rubberized grip for increased comfort on the job
- Sharp, pronounced spurs grip wood for controlled nailing at an angle
- Rubber bumpers protect the tool and surface from damage
- Nail lock-out mechanism protects tool and work surface from dry-fires

SPECIFICATIONS

Power Type	Pneumatio
Operating Air Pressure	
Minimum Recommended Air Delivery	6.2 SCFM @ 90 PS
Nail Size2"-3-1/2" .113"148" shank	diameter plastic collated
Maximum Magazine Capacity	73
Fastening category	Framing
Dimensions (LxWxH)	22" x 4-5/8" x 13-3/4"
Net Weight	8.3 lbs
UPC Code	088381-857093

STANDARD EQUIPMENT

- Safety Glasses
- Air Fitting
- Pneumatic Nailer Oil
- Hex Wrench

RELATED PRODUCTS

- 1. 5.5 HP* Big Bore™ Gas Air Compressor (MAC5501G)
- 2. 3.0 HP* Big Bore[™] Air Compressor (MAC5200)
- **3.** 7-1/4" Circular Saw (5007F)
- 4. 18V X2 LXT® (36V) Brushless 7-1/4" Circular Saw Kit (XSH06PT)
- 5. 18V X2 LXT® (36V) Brushless Rear Handle 7-1/4" Circular Saw Kit (XSR01PT)







