

CORDLESS PLUNGE SAW BLADES

FEATURES & BENEFITS

High Grade Carbide Tips
for Durability

Ultra-Thin Kerf for More
Cuts Per Charge

20 mm Arbor

Fully Hardened and Expertly
Hand-Tensioned Steel Saw
Plate for True Cuts

9,250 Max RPM



NEW ACCESSORY OVERVIEW

FEATURES

- Up to 140% more cuts per charge
- High-grade carbide tips for durability
- Laser cut slots for quieter cutting and less vibration
- Flourine Coating reduces pitch build-up for smoother cuts

PLUNGE SAW BLADES



B-57342



A-99932



A-99960



A-99982



A-99998



A-99976



A-98809

PART NO.	DESCRIPTION	KERF	RAKE ANGLE	PLATE THICKNESS	ARBOR	TEETH CONFIG./# OF TEETH	FLOURINE COATING	LASER SLOTS	UPC CODE (08381)
B-57342	6-1/2" 56T Carbide-Tipped Cordless Plunge Saw Blade, Wood, MDF	.057"	23°	.039"	20 mm	ATAFR 56	✓	✓	518437
A-99932	6-1/2" 48T Carbide-Tipped Cordless Plunge Saw Blade, Wood	.073"	8°	.049"	20 mm	ATB 48	-	✓	490375
A-99960	6-1/2" 28T Carbide-Tipped Cordless Plunge Saw Blade, Wood	.079"	23°	.055"	20 mm	ATB 28	-	-	495943
A-99982	6-1/2" 60T (ATB) Carbide-Tipped Cordless Plunge Saw Blade, MDF	.079"	5°	.055"	20 mm	Hi-ATB 60	✓	✓	495967
A-99998	6-1/2" 60T (TCG) Carbide-Tipped Cordless Plunge Saw Blade, MDF	.079"	5°	.055"	20 mm	TCG 60	✓	✓	495974
A-99976	6-1/2" 56T Carbide-Tipped Cordless Plunge Saw Blade, Aluminum.	.079"	-3°	.055"	20 mm	TCG 56	-	✓	495950
A-98809	6-1/2" 48T Carbide-Tipped Cordless Plunge Saw Blade, Corian®	.079"	5°	.055"	20 mm	TCG 48	-	✓	495981

RELATED ACCESSORIES

1. 55" Guide Rail (194368-5)
2. 118" Guide Rail (194367-7)
3. Rail Clamp Set, 2-Pc. (194385-5)
4. Guide Rail Connector (P-45777)
5. 55" Splinter Guard Replacement Strip (194418-6)



All specifications subject to change without prior notice. All models and accessories subject to stock on hand. The Makita Teal Color is the trade dress of Makita Corporation and is protected under common law and registered with the U.S. Patent and Trademark Office. NTF-1017 MA-3577-17