




# 5" SJS™II Angle Grinder with Tuck Point Guard

Model GA5040X1

## SJS™II ANGLE GRINDER WITH 5" TUCK POINT GUARD AND DIAMOND BLADE


- Powerful 10.0 AMP Motor Delivers More Output and 11,000 RPM
- SJS™II provides a mechanical gear drive system to help prevent motor and gear damage by dampening the force on the gear when the wheel is forced to stop
- SJS™II provides a leaf spring and cam gear drive mechanism that is engineered to reduce vibration for increased operator comfort during extended use
- Includes 5" dust extraction tuck point guard for clean & accurate tuck pointing and cutting

### POWER




Powerful 10.0 AMP motor delivers more output and 11,000 RPM

### DURABILITY



SJS™II provides a mechanical gear drive system to help prevent motor and gear damage

### COMFORT



SJS™II provides a leaf spring and cam gear drive mechanism that is engineered to reduce vibration

### VERSATILITY



Fully featured tuck point guard for precision cutting and dust extraction



# LESS VIBRATION

# 5" SJS™ II Angle Grinder with Tuck Point Guard

## Model GA5040X1

### FEATURES & BENEFITS

- Labyrinth construction seals and protects the motor and bearings from dust and debris for longer tool life
- "Tool-less" wheel guard for easy adjustment
- Zig-zag varnish protects the armature coil from dust and debris for longer tool life
- Spiral bevel gears for smoother rotations and a more efficient transfer of energy
- Slide switch with lock-on for continuous use
- Vibration absorbing side handle provides increased comfort on the job
- 5" dust extraction tuck point guard includes:
  - Easily adjustable depth setting for quick changes
  - Adjustable depth stops for added user convenience
  - Clear viewing window for improved visibility
  - Plunge feature allows for improved dust containment

### STANDARD EQUIPMENT

- 5" dust extracting tuck point guard (196845-3)
- 5" dual sandwich diamond tuck point blade (A-96017)
- Lock nut wrench (782412-6)
- Lock nut (224568-4)
- Inner flange (224399-1)
- Side handle (162258-0)
- "Tool-less" wheel guard (123145-8)
- Tuck guard hex wrench (783222A4)

### SPECIFICATIONS

	GA5040X1
Grinding wheel/ sanding disk	5"
Wire cup brush	3-1/2"
No load speed	11,000 RPM
Spindle thread	5/8"-11 UNC
AMPS	10
Lock-On	Yes
Lock-Off	No
Overall length	11-7/8"
Net weight	5.3 lbs.
Shipping weight	7.3 lbs.
UPC code	088381-698290



Model GA5040X1



### OPTIONAL ACCESSORIES

- Segmented blade, general purpose (A-94699)
- Turbo rim blade, general purpose (A-94568)
- Crack chaser, general purpose (D-09606)
- Tuck point blade, general purpose (A-96017)



Makita offers a wide variety of accessories. For a complete listing, please refer to the Makita General Catalog or visit our website at [makitatools.com](http://makitatools.com), or call 1-800-4MAKITA.

All specifications subject to change without prior notice. All models and accessories subject to stock on hand.  
The Makita Teal Color is the trade dress of Makita Corporation and is protected under common law and registered with the U.S. Patent and Trademark Office  
NTF-0315.MA5059-15A