

1-3/16" ROTARY HAMMER, ACCEPTS SDS-PLUS BITS (L-SHAPE)



NEW TOOL OVERVIEW HR3001CK



FEATURES

- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- "L-shape" body design brings the operator closer to the application for increased accuracy
- Vibration-absorbing back handle for operator comfort
- Dust extraction capability with optional Makita Dust Attachment
- Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears if the bit binds
- Variable speed trigger enables user to match the speed to the application for greater versatility
- Bit angle settings allow the steel bit to be set at different positions while performing hammer only applications
- Recessed hammer function selector for improved durability
- Extended life brushes for more work between service intervals and less downtime

SPECIFICATIONS

| | |
|--|------------------|
| AMPS | 7.5 |
| Max. Capacity (concrete drilling) | 1-3/16" |
| Optimum Range (concrete drilling) | 1/4" - 5/8" |
| Max. Capacity (concrete drilling w/ core bit) | 3-1/8" |
| Impact Energy (ft.lbs.) | 2.9 |
| Impact Energy (Joules) | 3.9 J |
| Blows Per Minute (variable speed) | 0 - 4,500 BPM |
| No Load Speed (variable speed) | 0 - 840 RPM |
| Vibration Control | Yes |
| Vibration (m/s²) | 16.5 |
| Overall Length | 14" |
| Cord Length (ft) | 8.2' |
| Net Weight | 9 lbs. |
| Bit Type | Accepts SDS-PLUS |
| Power Type | Corded |
| UPC Code | 088381-896825 |

PRODUCT HIGHLIGHTS



POWER

Powerful 7.5 AMP motor delivers 2.6 ft.lbs. of impact energy to handle demanding applications



VERSATILITY

3-mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only"



PERFORMANCE

Vibration-absorbing back handle for operator comfort



ERGONOMICS

Ergonomic rubberized soft-grip handle with large multi-finger trigger provide increased comfort

STANDARD EQUIPMENT

- Depth Gauge (331886-4)
- Side Handle Assembly (127220-2)
- Tool Case

RELATED PRODUCTS

1. 1-3/16" AVT® Rotary Hammer, accepts SDS-PLUS bits (L-Shape) (HR3011FCK)
2. 1" AVT® Rotary Hammer (HR2641)
3. 18V X2 LXT® 36V Brushless 1-1/8" AVT® Rotary Hammer Kit, AFT®, AWS™ Capable (XRH10PTW)
4. 5/8" x 10" SDS-PLUS Bit, 3-Cutter (B-61139)
5. Dust Extraction Cup (195173-3)

1

2

3

4

5

