5" SJS™II COMPACT CONCRETE PLANER WITH DUST EXTRACTION SHROUD AND DIAMOND CUP WHEEL



PRODUCT HIGHLIGHTS



PERFORMANCE

Constant Speed Control automatically applies additional power to maintain speed under load



COMFORT

SJS™II provides a drive mechanism that is engineered to reduce vibration for increased comfort



DUST MANAGEMENT

Integrated dust extraction shroud is designed to capture dust during concrete surfacing applications



ERGONOMICS

Ergonomic loop handle and barrel grip for maximum operator comfort

77700 OVERVIEW PC5010CX1



FEATURES

- Powerful 12.0 AMP motor delivers more output and (4,000 9,000) RPM
- Variable speed control dial allows manual RPM adjustment (4,000-9,000) to match the speed to the application
- Soft Start suppresses start-up reaction for smooth start-ups and longer gear life
- Electronic Current Limiter helps protect the motor from overload in high torque applications
- Anti-Restart Protection prevents accidental start-up even if the tool is plugged to power source in the on position
- · Removable dust shroud cap allows for flush-to-wall edge grinding
- 4-spring suspension system keeps shroud flush with surface during movement
- Soft brushes help prevent dust from escaping and help move the tool over the surface

SPECIFICATIONS

Wheel Diameter	5"
No Load Speed (variable speed)	4,000 - 9,000 RPM
AMPS	12
Overall Length	13-3/4"
Constant speed control	
Spindle Thread	5/8" - 11 UNC
Soft start	Yes
Electric current limiter	Yes
Switch Type	Body grip/slide
Lock-On Switch	Yes
Lock-Off Switch	No
Net Weight	5.5 lbs.

STANDARD EQUIPMENT

- 4-1/2" Low-Vibration Diamond Cup Wheel (A-96403)
- Lock Nut Wrench (782425-7)
- 5" Dust Extraction Surface Grinding Shroud

RELATED PRODUCTS

- 1. 4-1/2 5" Front Edge Cover (451765-1)
- 2. Replacement Brush Set (196880-1)
- 3. 5" Low-Vibration Diamond Cup Wheel, Turbo (A-98871)
- 4. 12 Gallon Xtract Vac® Wet/Dry Dust Extractor/Vacuum (VC4710)
- 5. 18V X2 LXT® (36V) 2.1 Gallon HEPA Filter Dry Dust Extractor/Vacuum (XCV04Z)









