

**18V LXT® LITHIUM-ION BRUSHLESS CORDLESS  
4-1/2" / 5" PADDLE SWITCH CUT-OFF/ANGLE  
GRINDER, WITH ELECTRIC BRAKE AND AWS™,  
TOOL ONLY**



**NEW TOOL OVERVIEW  
XAG21ZU**

**LXT® BRUSHLESS**

**FEATURES**

- Electric Brake stops the grinding or cut-off wheel in 2 seconds or less for maximum productivity
- Electronic Torque Control turns the motor off if rotation speed suddenly slows or wheel is forced to stop
- Automatic-start Wireless System (AWS) utilizes Bluetooth™ technology for wireless power-on/off communication between tool and dust extractor
- Automatic Speed Change™ technology adjusts speed and torque during operation for optimum performance
- The BL™ Brushless Motor eliminates carbon brushes, enabling the BL™ Motor to run cooler and more efficiently for longer life
- Variable speed control dial allows manual RPM adjustment (3,000-8,500) to match the speed to the application

**SPECIFICATIONS**

<b>Wheel Diameter</b> .....	5"
<b>Battery</b> .....	18V LXT® Lithium-Ion
<b>No Load Speed (variable speed)</b> .....	3,000 - 8,500 RPM
<b>Spindle Thread</b> .....	5/8" - 11 UNC
<b>Lock-On</b> .....	No
<b>Lock-Off</b> .....	Yes
<b>Switch Type</b> .....	Body grip/paddle
<b>Electric Brake</b> .....	Yes
<b>Variable speed control dial</b> .....	Yes
<b>Overall Length</b> .....	15"
<b>Net Weight (with battery)</b> .....	5.7 lbs.
<b>Shipping Weight</b> .....	7.6 lbs.
<b>UPC Code</b> .....	088381-854177
<b>Power Type</b> .....	Cordless

**STANDARD EQUIPMENT**

- 5" x 1/4" x 7/8" INOX Grinding Wheel, 36 Grit (A-95962)
- 5" Cut-Off Wheel Guard (126686-3)
- 5" Tool-less Wheel Guard (126687-1)
- Lock Nut Wrench (782424-9)
- Auto-Start Wireless Unit (198901-5)
- Side Handle (158237-4)



**PRODUCT HIGHLIGHTS**



**PRODUCTIVITY**

Electric Brake stops the grinding or cut-off wheel in 2 seconds or less for maximum productivity



**TECHNOLOGY**

AWS™ for wireless power-on/off communication with dust extractor



**CONTROL**

Electronic Torque Control turns the motor off if wheel is forced to stop



**VERSATILITY**

Variable speed control dial allows manual RPM adjustment (3,000-8,500)

**RELATED PRODUCTS**

1. 5" Dust Extraction Tuck Point Guard (196846-1)
2. 4-1/2" - 5" Dust Extraction Cutting Guard (193794-5)
3. 4-1/2" - 5" Dust Extraction Cutting Guard (192618-2)
4. 4-1/2"-5" Dust Extraction Surface Grinding Shroud (195236-5)
5. 18V X2 LXT® (36V) Brushless 2.1 Gallon HEPA Filter Dry Dust Extractor, with AWS™ (XCV08Z)

