36V (18V X2) LXT® BRUSHLESS BLOWER KIT (5.0Ah)







- Delivers up to 28 minutes of run time at mid-speed (15,800 RPM) using two 18V LXT® 5.0Ah batteries
- BL[™] Brushless motor delivers up to 120 MPH air velocity and 473 CFM of air volume
- Sound pressure rating of 61 dB(A); measured per ANSI B 175.2 standard
- Zero emissions and reduced maintenance; no need for gas or oil
- 6-stage air velocity/volume selection dial with variable speed control trigger
- Two 18V LXT® Lithium-Ion batteries deliver the power and run time for gas powered demands without leaving the 18V LXT® platform
- Compact and ergonomic design at only 36-5/8" long
- · Weighs only 9.0 lbs. with batteries for reduced operator fatigue

SPECIFICATIONS Max. Air Volume 473 CFM Max. Air Velocity 120 MPH Sound Pressure (per Ansi B175.2 standard) 61 dB(A) Overall Length 36-5/8" Net Weight (with battery) 9 lbs. Battery 2X 18V LXT® Lithium-lon Shipping Weight 19 lbs. UPC Code 088381-847537

PRODUCT HIGHLIGHTS



POWER

ALSO AVAILABLE AS A BARE TOOL: XBU02Z

BL™ Brushless motor delivers up to 120 MPH air velocity and 473 CFM of air volume



VERSATILITY

6-stage air velocity/volume selection dial with variable speed control trigger

WARRANTY

TOOL &



INNOVATION

Two 18V LXT® Lithium-lon batteries deliver the power and run time for gas powered demands



CONVENIENCE

Sound pressure rating of 61 dB(A); measured per ANSI B 175.2 standard

STANDARD EQUIPMENT

XBU02PT

- 36V (18V X2) LXT® Brushless Blower (XBU02Z)
- (2) 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850B)
- 18V LXT® Lithium-Ion Dual Port Charger (DC18RD)
- 3-Stage Telescoping Blower Nozzle (183R02-0)

XBU02Z

- 36V (18V X2) LXT® Brushless Blower (XBU02Z)
- 3-Stage Telescoping Blower Nozzle (183R02-0)

RELATED PRODUCTS

- 1. Flat End Nozzle (197889-6)
- 2. Extension Attachment (197888-8)
- 3. 3-Stage Telescoping Blower Nozzle (183R02-0)
- 4. Shoulder Strap (166094-6)
- 5. 18V LXT® Lithium-Ion 5.0Ah Battery, 2/pk (BL1850B-2)

