18V X2 (36V) LXT[®] LITHIUM-ION BRUSHLESS CORDLESS 14" CHAIN SAW KIT WITH 4 BATTERIES (5.0AH)



PRODUCT HIGHLIGHTS



POWER Makita-built Outer Rotor BL™ Brushless Motor direct-drive system provides high power efficiencv



SPEED Variable speed trigger and high chain speed (0-3,940 FPM) for improved cutting performance



DESIGN

Compact rear handle design offers improved performance and operator comfort

"Tool-less" chain

INNOVATION

adjustment for convenient operation and maintenance

Thakita **NEW TOOL OVERVIEW** XCU03PT1



FEATURES

- Makita-built Outer Rotor BL[™] Brushless Motor direct-drive system provides high power efficiency equivalent to gas chain saw
- Variable speed trigger and high chain speed (0-3,940 FPM) for improved cutting performance
- "Tool-less" chain adjustment for convenient operation and maintenance
- Built-in lock-off lever helps prevent the chain from accidentally engaging
- Built-in L.E.D. on/off switch with auto power-off function; automatically shuts the saw off when operation is delayed for extended battery life
- Two 18V LXT[®] Lithium-Ion batteries deliver power and • performance without leaving the 18V LXT® platform

SPECIFICATIONS

| Guide Bar Length | |
|----------------------------|-------------------------|
| Chain Speed | |
| Chain Pitch | |
| Chain Gauge | |
| Battery | 2X 18V LXT® Lithium-Ion |
| Overall Length | |
| Net Weight (with battery) | 11.5 lbs. |
| Shipping Weight (XCU03PT1) | |
| Shipping Weight (XCU03Z) | |
| UPC Code (XCU03PT1) | |
| UPC Code (XCU03Z) | |

STANDARD EQUIPMENT

- (4) 18V LXT[®] Lithium-Ion 5.0Ah Battery (BL1850B) •
- 18V LXT® Lithium-Ion Dual Port Charger (DC18RD) •
- 14" Guide Bar 3/8"-.043" •
- Chain •
- Guide Bar Cover



RELATED ACCESSORIES

2. 14" Guide Bar (165201-8)

4. 16" Guide Bar (442-040-661)



1. Combo Safety Helmet (986-200-002) 2 3 5 Δ 3. 14" Saw Chain, 3/8"-.050" (196207-5) 5. 16" Saw Chain, 3/8"-.050" (196208-3)

makitatools.com