18V LXT® LITHIUM-ION BRUSHLESS CORDLESS AVT® POWER SCRAPER KIT,

ACCEPTS SDS-PLUS (5.0Ah)



PRODUCT HIGHLIGHTS



POWER

BL™ Brushless motor delivers 2.2 ft.lbs. of impact energy to handle the most demanding applications



APPLICATIONS

Variable speed dial and trigger enables user to match the speed to the application



COMFORT

Anti-Vibration Technology is a vibration absorbing housing which effectively isolates vibration



CONVENIENCE

Built-in L.E.D. light with an independent on/off illuminates the work area





FEATURES

- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- Lock-on power mode for continuous operation
- Soft start suppresses start-up reaction for more precision and better accuracy
- Extreme Protection Technology (XPT™) is engineered for improved dust and water resistance for operation in harsh conditions
- Ergonomic soft-grip handle and large 3-finger trigger provide increased comfort on the job
- 12 bit angle settings allow the bit to be set at different positions for operating convenience
- · Retractable hang hook/tether loop secures the tool when not in use
- · Weighs only 7.7 lbs. with batteries for reduced operator fatigue

SPECIFICATIONS

Battery	18V LXT® Lithium-Ion
Blows Per Minute (variable speed)	0 - 3,200 BPM
Impact Energy (ft.lbs.)	2.2
Impact Energy (Joules)	3.1 J
Vibration Control	Yes
Vibration (m/s²)	4.5
Noise Level	83 dB
Overall Length	14-1/2"
Net Weight	
Bit Type	Accepts SDS-PLUS
Power Type	Cordless
UPC Code	381-891448 (XKU01TJ)
UPC Code088	3381-891455 (XKU01Z)

STANDARD EQUIPMENT

- 18V Brushless AVT® Power Scraper, Tool Only (XKH01Z)
- (2) 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850B)
- 18V LXT® Lithium-Ion Rapid Optimum Charger (DC18RC)
- Tool Case

RELATED PRODUCTS

- 1. 4" Floor Scraper Blade and Assembly, SDS-PLUS (A-30106)
- 2. 2" x 8-1/2" Scaling Chisel, SDS-PLUS (D-51166)
- 3. 3/4" x 10" Cold Chisel, SDS-PLUS (D-51150)
- 4. 10" Bull Point, SDS-PLUS (D-51144)
- 5. Power Scraper (HK1810)

