

**18V X2 LXT® LITHIUM-ION (36V) BRUSHLESS
CORDLESS 1-1/8" AVT® ROTARY HAMMER KIT,
ACCEPTS SDS-PLUS BITS (5.0AH)**



AVT®
Anti Vibration Technology

5.0 Ah
BATTERY

3
YEAR
WARRANTY
LITHIUM-ION
TOOL & BATTERY


ALSO AVAILABLE AS A BARE TOOL: XRH08Z

PRODUCT HIGHLIGHTS



PERFORMANCE

X2 LXT® technology delivers up to 140 1/2" x 2-3/8" holes per charge using two 18VLXT® 5.0Ah batteries




COMFORT

AVT® is an active internal counterbalance system engineered to reduce vibration



DUST MANAGEMENT

Dust extraction capability with optional OSHA Table 1 compliant on-board Dust Extractor



POWER

Constant speed control automatically applies additional power to maintain speed under load

RELATED PRODUCTS

1. Dust Extractor Attachment with HEPA Filter (DX08)
2. Dust Extraction Cup (195173-3)
3. 18V X2 LXT® (36V) Brushless Backpack Dust Extractor/Vacuum (XCV05ZX)
4. 18V X2 LXT® (36V) 2.1 Gallon HEPA Filter Dry Dust Extractor/Vacuum (XCV04Z)
5. 1/2" x 6" SDS-PLUS Bit, 3-Cutter, 10/pk (B-61276)



All specifications subject to change without prior notice. All models and accessories subject to stock on hand. The Makita Teal Color is the trade dress of Makita Corporation and is protected under common law and registered with the U.S. Patent and Trademark Office. **NTF-0818 MA-5036-18**



**NEW TOOL OVERVIEW
XRH08PT**

**LXT® X2 18V + 18V 36V
BRUSHLESS**

FEATURES

- Powerful BL™ Brushless motor delivers 0-980 RPM, 0-5,000 BPM and 2.3 ft.lbs. of impact energy to handle the most demanding applications
- Vibration-absorbing back handle and side handle further reduce vibration and increase comfort on the job
- Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears if the bit binds
- Variable speed dial and trigger enables user to match the speed to the application
- Built-in L.E.D. light with an independent on/off illuminates the work area
- Ergonomic soft-grip handle and large 2-finger trigger provide increased comfort on the job

SPECIFICATIONS

Max. Capacity (concrete drilling)	1-1/8"
Optimum Range (concrete drilling)	3/16" - 5/8"
Max. Capacity (concrete drilling w/ core bit)	2-1/8"
Impact Energy (ft.lbs.)	2.3
Impact Energy (Joules)	3.2 J
Blows Per Minute (variable speed)	0 - 5,000 BPM
No Load Speed (variable speed)	0 - 980 RPM
Vibration Control	Yes
Vibration (m/s²)9
Battery	2X 18V LXT® Lithium-Ion
Overall Length	14-3/4"
Net Weight (with battery)	10.8 lbs.
Bit Type	Accepts SDS-PLUS
Power Type	Cordless
UPC Code (XRH08Z)	088381-857932
UPC Code (XRH08PT)	088381-865142

STANDARD EQUIPMENT

- XRH08Z - Tool Only
- (2) 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850B)
- 18V LXT® Lithium-Ion Dual Port Charger (DC18RD)
- Side Handle
- Depth Gauge
- Tool Bag