

**18V X2 LXT® LITHIUM-ION (36V) BRUSHLESS  
CORDLESS 1-1/8" AVT® ROTARY HAMMER, ACCEPTS  
SDS-PLUS BITS, AFT®, AWS™ CAPABLE, TOOL ONLY**



**NEW TOOL OVERVIEW  
XRH11Z**

**AFT®**



**3  
YEAR  
WARRANTY  
LITHIUM-ION  
TOOL &  
BATTERY**

**LXT® X2 18V + 18V 36V  
BRUSHLESS**

**FEATURES**

- Powerful BL™ Brushless motor delivers 0-980 RPM, 0-5,000 BPM and 2.3 ft.lbs. of impact energy to handle the most demanding applications
- Auto-Start Wireless System (AWS™) which utilizes Bluetooth® technology for wireless power-on/off communication between tool and dust extractor
- AWS™ capable with Auto-Start Wireless Transmitter (part no. 198901-5) sold separately
- Anti-Vibration Technology (AVT®) is an active internal counterbalance system which is engineered to reduce vibration for increased comfort
- Vibration absorbing side handle provides increased comfort on the job
- Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears if the bit binds
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs

**SPECIFICATIONS**

<b>Max. Capacity (concrete drilling)</b> .....	1-1/8"
<b>Optimum Range (concrete drilling)</b> .....	3/16" - 5/8"
<b>Max. Capacity (concrete drilling w/ core bit)</b> .....	2-1/8"
<b>Impact Energy (ft.lbs.)</b> .....	2.3
<b>Impact Energy (Joules)</b> .....	3.2 J
<b>Blows Per Minute (variable speed)</b> .....	0 - 5,000 BPM
<b>No Load Speed (variable speed)</b> .....	0 - 980 RPM
<b>Vibration Control</b> .....	Yes
<b>Vibration (m/s<sup>2</sup>)</b> .....	9.5
<b>Battery</b> .....	2X 18V LXT® Lithium-Ion
<b>Overall Length</b> .....	15-7/8"
<b>Net Weight (with battery)</b> .....	11.2 lbs.
<b>Bit Type</b> .....	Accepts SDS-PLUS
<b>UPC Code</b> .....	088381-861977

**PRODUCT HIGHLIGHTS**



**PERFORMANCE**

X2 LXT® technology delivers up to 140 1/2"x2-3/8" holes per charge using two 18VLXT® 5.0Ah batteries (batteries not included)



**CONTROL**

AFT® electronically turns off the motor if rotation of bit is suddenly forced to stop



**DUST MANAGEMENT**

Dust extraction capability with optional OSHA Table 1 compliant On-Board Dust Extractor



**VERSATILITY**

Quick change chuck allows easy interchangeability from SDS-PLUS to 1/2" keyless chuck

**STANDARD EQUIPMENT**

- Side Handle
- Depth Gauge
- 1/2" Drill Chuck

**RELATED PRODUCTS**

1. Dust Extraction Cup (195179-1)
2. Auto-Start Wireless Transmitter (198901-5)
3. 18V X2 LXT® (36V) Brushless 2.1 Gal. HEPA Filter Dry Dust Extractor/Vacuum, AWS™ (XCV08Z)
4. Dust Extractor Attachment with HEPA Filter (DX09)
5. 1/2" x 6" SDS-PLUS Bit, 3-Cutter, 10/pk (B-61276)

