

18V X2 LXT® (36V) BRUSHLESS CORDLESS 1-1/8" AVT® ROTARY HAMMER KIT, ACCEPTS SDS-PLUS BITS W/ HEPA DUST EXTRACTOR (5.0AH)

OSHA 
COMPLIANT



5.0 Ah
BATTERY

3
YEAR
WARRANTY
LITHIUM-ION
TOOL & BATTERY


ALSO AVAILABLE AS A BARE TOOL: XRH08Z

PRODUCT HIGHLIGHTS



PERFORMANCE

X2 LXT® technology delivers up to 140 1/2" x 2-3/8" holes per charge using two 18V LXT® 5.0Ah batteries




COMFORT

AVT® is an active internal counterbalance system engineered to reduce vibration



DUST MANAGEMENT

OSHA Table 1 compliant on-board dust extractor has a filter cleaning mechanism for optimum suction



POWER

Constant speed control automatically applies additional power to maintain speed under load

RELATED PRODUCTS

1. Dust Extraction Cup (195173-3)
2. 18V X2 LXT® (36V) Brushless Backpack Dust Extractor/Vacuum (XCV05ZX)
3. 18V X2 LXT® (36V) 2.1 Gallon HEPA Filter Dry Dust Extractor/Vacuum (XCV04Z)
4. 3/8" x 6" SDS-PLUS Bit, 3-Cutter, 10/pk (B-61254)
5. 1/2" x 6" SDS-PLUS Bit, 3-Cutter, 10/pk (B-61276)



All specifications subject to change without prior notice. All models and accessories subject to stock on hand. The Makita Teal Color is the trade dress of Makita Corporation and is protected under common law and registered with the U.S. Patent and Trademark Office. **NTF-0818 MA-5141-18**

makitatools.com

Makita

NEW TOOL OVERVIEW XRH08PTW

LXT ^{X2 18V + 18V 36V} **BRUSHLESS**

FEATURES

- Powerful BL™ Brushless motor delivers 0-980 RPM, 0-5,000 BPM and 2.3 ft.lbs. of impact energy to handle the most demanding applications
- Vibration-absorbing back handle and side handle further reduce vibration and increase comfort on the job
- Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears if the bit binds
- Electric brake allows the tool to be repositioned faster for maximum productivity
- Variable speed dial and trigger enables user to match the speed to the application
- Built-in L.E.D. light with an independent on/off illuminates the work area
- Ergonomic soft-grip handle and large 2-finger trigger provide increased comfort on the job
- 3-mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications

SPECIFICATIONS

Max. Capacity (concrete drilling)	1-1/8"
Optimum Range (concrete drilling)	3/16" - 5/8"
Max. Capacity (concrete drilling w/ core bit)	2-1/8"
Impact Energy (ft.lbs.)	2.3
Impact Energy (Joules)	3.2 J
Blows Per Minute (variable speed)	0 - 5,000 BPM
No Load Speed (variable speed)	0 - 980 RPM
Vibration Control	Yes
Vibration (m/s²)9
Battery	2X 18V LXT® Lithium-Ion
Overall Length	14-3/4"
Net Weight (with battery)	10.8 lbs.
Bit Type	Accepts SDS-PLUS
Power Type	Cordless
UPC Code (XRH08PTW)	088381-878333
UPC Code (XRH08Z)	088381-857932

STANDARD EQUIPMENT

- XRH08Z - Tool Only
- Dust Extractor Attachment with HEPA Filter Cleaning Mechanism (DX08)
- (2) 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850B)
- 18V LXT® Lithium-Ion Dual Port Charger (DC18RD)
- Side Handle
- Depth Gauge
- Tool Bag