18V LXT® LITHIUM-ION BRUSHLESS CORDLESS JIG SAW, TOOL ONLY





PRODUCT HIGHLIGHTS



COMPACT

Most compact and lightweight Jig Saw in Makita LXT class; weighs only 3.8 lbs. (tool only)



PERFORMANCE

Brushless motor delivers 0 - 3,000 Strokes Per Minute for a variety of cutting applications



ACCURACY

Variable speed trigger, speed dial and soft noload mode provides more accurate cutting



CONVENIENCE

Tool-less blade change lever allows for convenient blade installation and removal

LXT BRUSHLESS

FEATURES

- Makita-built brushless variable speed motor delivers 0-3,000 strokes per minute for faster and more efficient cutting
- 3 orbital settings plus straight cutting for use in a wide range of materials
- Soft no-load mode creates a more accurate starting cut by slowing increasing the speed of the blade when it engages the material
- Built-in L.E.D. light illuminates the work area
- Large 2-finger variable speed trigger for added convenience with lock-on button
- Electric brake for maximum productivity
- Soft start feature for smooth start-ups
- · Built-in dust blower clears the line of cut for increased accuracy

SPECIFICATIONS

Length of Stroke	7/8"
Max. Cutting Capacity at 90° (wood)	5-5/16"
Max. Cutting Capacity at 90° (steel)	3/8"
Max. Cutting Capacity at 90° (aluminum).	25/32"
Strokes Per Minute (variable speed)	0 - 3,000 SPM
Blade Shank	"T" Tang
Battery	18V LXT® Lithium-Ion
Overall Length	10-1/8"
Net Weight (with battery)	5.2 lbs.
Shipping Weight	4.83 lbs.
UPC Code	088381-762557

STANDARD EQUIPMENT

- 18V LXT®Brushless Jig Saw. Tool Only (XVJ04Z)
- Jig Saw Blade B-50, T Shank, 3-15/16" x 9TPI, Wood Cutting
- Jig Saw Blade B-51, T Shank, 3-15/16" x 14TPI, Metal Cutting
- Jig Saw Blade B-52, T Shank, 3-15/16" x 9TPI, Wood/Metal Cutting

RELATED PRODUCTS

- 1. 18V LXT® Lithium-Ion 4.0Ah Battery (BL1840)
- 2. 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850)
- 3. Jig Saw Blade, T Shank, HSS, 3" x 24TPI, 5/pk (792473-8)
- 4. Jig Saw Blade, T Shank, HSS 3-1/2" x 24TPI, 5/pk (792428-3)
- 5. Jig Saw Blade, T Shank, HCS, 7-1/8" x 6TPI, 5/pk (792730-4)

