

18V LXT® LITHIUM-ION BRUSHLESS CORDLESS 4-SPEED 3/8" SQ. DRIVE IMPACT WRENCH W/ FRICTION RING ANVIL (5.0AH)



ALSO AVAILABLE AS A BARE TOOL: XWT16Z

5.0Ah BATTERY

3
YEAR
WARRANTY
LITHIUM-ION
TOOL & BATTERY

PRODUCT HIGHLIGHTS



POWER

Brushless motor delivers 220 ft.lbs. of Fastening Torque and 370 ft.lbs. of Nut-Busting Torque



CONTROL

4-speed power selection for precise fastening control in a wide range of applications



INNOVATION

3 forward and 3 reverse Auto-Stop modes for increased efficiency



COMFORT

Weighs only 4.0 lbs. with battery for reduced operator fatigue

RELATED PRODUCTS

1. Impact XPS® 10 Pc. 3/8" Drive 6-Point Metric Impact Socket Set w/ Socket Adapter (E-01688)
2. Impact XPS® 10 Pc. 3/8" Drive 6-Point SAE Impact Socket Set w/ Socket Adapter (E-01672)
3. 18V LXT® Lithium-Ion Rapid Optimum Charger (DC18RC)
4. 18V LXT® Lithium-Ion Compact 2.0Ah Battery (BL1820B)
5. 18V LXT® Lithium-Ion 6.0Ah Battery (BL1860B)



NEW TOOL OVERVIEW XWT16T

LXT® BRUSHLESS

FEATURES

- Makita-built Brushless Motor delivers 220 ft.lbs. of Fastening Torque and 370 ft.lbs. of Nut-Busting Torque
- Compact and ergonomic design at only 5-1/2" long
- 4-speed power selection switch (0-1,000 / 0-1,800 / 0-2,600 / 0-3,200 RPM & 0-1,800 / 0-2,600 / 0-3,400 / 0-4,000 IPM) for precise fastening control in a wide range of applications
- 3 forward and 3 reverse Auto-Stop modes for increased efficiency
- Full speed mode function reduces trigger pull to reach full speed
- Efficient BL™ Brushless Motor is electronically controlled to optimize battery energy use for up to 50% longer run time per charge
- The electronically-controlled BL™ Brushless Motor efficiently uses energy to match torque and RPM to the changing demands of the application
- Extreme Protection Technology (XPT™) is engineered to provide improved dust and water resistance for operation in harsh conditions

SPECIFICATIONS

Battery	18V LXT® Lithium-Ion
Voltage	18V
Square Drive	3/8"
No Load Spd. (var. 4 spd.)	0-1,000/0-1,800/0-2,600/0-3,200 RPM
Impacts Per Min. (var. 4 spd.)	0-1,800/0-2,600/0-3,400/0-4,000 IPM
Nut-Busting Torque (ft.lbs./N•m)	370 ft.lbs./500 N•m
Fastening Torque (ft.lbs./N•m)	220 ft.lbs./300 N•m
Overall Length	5-1/2"
Net Weight (with battery)	4 lbs.
Shipping Weight	9.09 lbs.
UPC Code	088381-748766

STANDARD EQUIPMENT

XWT16T

- 18V LXT® Lithium-Ion Brushless Cordless 4-Speed 3/8" Sq. Drive Impact Wrench w/ Friction Ring Anvil(XWT16Z)
- 18V LXT® Lithium-Ion Rapid Optimum Charger (DC18RC)
- (2) 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850B)
- Tool Bag

XWT16Z

- 18V LXT® Lithium-Ion Brushless Cordless 4-Speed 3/8" Sq. Drive Impact Wrench w/ Friction Ring Anvil(XWT16Z)